568-17

CV Multi-Colour Additive, clear



Application:





cabs (refurbishing), boxes, busses (repair), sign writing this product is used in:

- 284-13
- 284-45
- 924-68
- 68 line

Key Features:

- · good leveling
- · fast to assemble
- · quick-drying for multicolor painting with 68 Line

Remarks:

The substrate should be clean, free of dust, rust, oil and grease.

Substrates

- ●● = Very well suited
- = well suited
- suited in some cases

Galvanized steel

Steel

Staineless steel

Aluminium Anodized Aluminium

PP-EPDM

GRP / SMC

Glasurit CV - Primer Glasurit CV - Primer Filler

Powder coating

Plywood

Coil-coating

Mood

0EM-Paintwork

Old paint work

Drying

Remark

Use adhesion promoter 284-10 after 8 h at 20° C or oven drying. The maximum amount of 568-17 should only be 50% of the used reducer (premix of 568-17 and 352-... 1:1).

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 μm .

The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

568-17

CV Multi-Colour Additive, clear



Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

It cannot be ruled out that this product contains particles < $0.1 \mu m$.

The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.