




TECHNICAL INFORMATION

568-96 Glasurit Express Reducer for 9-7 clear

Z

Range of application:



construction machinery (steel), chassis painting (steel / aluminum)

Performance:

- suitable for large areas / surfaces
- fast drying

Special remarks:

It cannot be ruled out that this product contains particles < 0.1 µm
The products are suitable for professional use only.

Remarks:

Aluminum-Chassis have be primed with a suitable primer
Find addition information in the technical data sheet of 9-7



Painting process

CV 4, CV 7

Spreading rate

Solid content 10 %



Mixing ratio

4 : 1 by volume



Hardeners



Reducer

568-96	15 - 20°C
568-96	20 - 25°C
568-96	25 - 30°C



Viscosity DIN 4 / 20° C

18 - 20 s. DIN 4

Remarks

! To be used in 9-7 only

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.