


839-45

CV Flexible Body Filler, light grey



A brand of BASF –
We create chemistry

Application:



all applications

Key Features:

- suitable for large areas / surfaces
- high flexible alignment for welding seams
- long pot life
- temperature resistance up to 180°C

Remarks:

The substrate should be clean, free of dust, rust, oil and grease.

Substrates

- = Very well suited
- = well suited
- = suited in some cases

●●	Steel	Galvanized steel	●●	Stainless steel	●●	Aluminium	●	Anodized Aluminium	●	GRP / SMC	●	PP-EPDM	●	Glasurit CV - Primer	●	Glasurit CV - Primer Filler / Filler	●	Powder coating	●	Coil-coating	●	Plywood	●●	Wood	●	OEM-Paintwork	●	Old paint work
----	-------	------------------	----	-----------------	----	-----------	---	--------------------	---	-----------	---	---------	---	----------------------	---	--------------------------------------	---	----------------	---	--------------	---	---------	----	------	---	---------------	---	----------------

Solid Content ~ 98 %

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

2004/42/IIIB (b)(250)180: The EU limit value for this product (product category: IIB.b) in ready to use form is max. 250 g/l. The VOC content of this product is 180 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

839-45

CV Flexible Body Filler, light grey



A brand of BASF –
We create chemistry



Mixing Ratio 100 : 3 % by weight



Hardener 948-36

Potlife at 20°C 20 min



Drying	Overcoatable		Tack-free	Ready for masking	Ready to assemble	Sandable
	Min.	Max.				
Object Temp. 20°C						2.5 h

Remark

Sandable after 2,5 hours.
Highly flexible product, for example for weld seams on tankers. Temperature resistant up to 180°C.
On zinc, before body-filling, see variant with EP 801-705 CV Primer Filler or variant with 284-13 CV primer filler.
Do not use on wash primer or acid-pre-treated surfaces!

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

2004/42/IIIB (b)(250)180: The EU limit value for this product (product category: IIB.b) in ready to use form is max. 250 g/l. The VOC content of this product is 180 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.